



145 1/2" ND EXT.
159-1/2" W/EXT.

5'-5"

1'-2"

40'-0" 9140
36'-8" 9136
30'-0" 9130

47 1/4"

30'-3 1/2" (9140)
26'-11 1/2" (9136)
20'-3 1/2" (9130)

2'-6 1/2"

129 1/2" ND EXT.
143 1/2" W/EXT.

HYD. SPECS.
40 GPM @ 3500 PSI PEAK PRESSURE
TRUCK ENGINE RPM 1500
RELIEF VALVE INSTALLED, SET AT 3500 PSI
40 GALLON RESERVOIR WITH OIL

PHYSICAL SPECS.
CAPACITY 80,000# GVW
EMPTY WEIGHT 16,000# (9136T)
TIRE SIZE-425/65R X 22.5
ALUMINUM 10-HOLE DISC WHEELS

MATERIAL:

TOLERANCE:
±1/32 UNLESS
OTHERWISE SPECIFIED

MEYER MFG. CORP.

TITLE 9140T/9136T/9130T TRAILER

425/65R TIRES

REV. DATE DESCRIPTION

1 4-28-08 HYD SPECS 3500 TO 3500, RELIEF VALVE 3500 TO 3500

2 6-22-09 HYD SPECS TO INCLUDE OIL AND RELIEF VALVE

SCALE DWG. BY JAA APPROVED BY

DATE 6/23/2009 DWG. NO. 9100T TRAILER MDUNT BOX